

EXTREME PRESSURE ANTI-WEAR AGENTS

PSAIL® SERIES

Luoyang Pacific United Petrochemical Co., Ltd.

UNPChemicals
No. 113, Huayang Avenue, Baihe Town,
Mengjin District, Luoyang City
Henan Province, China
86-379-67877555 sales@unpchemicals.com
www.unpchemicals.com

PSAIL[®] 3880 is an ashless anti-wear additive with excellent antioxidant properties. It can be used as a substitute for zinc dialkyldithiophosphate in the formulation of metalworking fluids and industrial oils that do not require metals such as zinc. In the field of metalworking, the combination of this product and sulfur carrier significantly enhances the surface finish of the workpiece and extends tool life.

CHEMICAL COMPOSITION

Amine dialkyldithiophosphate CAS No.: 71888-91-0

TYPICAL PROPERTIES

Test Item	Typical Data	Method
Appearance	Yellow clarified liquid	Visual inspection
Density at 20℃, g/cm³	0.94	GB/T 1884-2000
Flash point open cup, ℃	>130.0	GB/T 3536-2008
Phosphorus content, %	5.0	NB/SH/T 0824-2010
Sulfur content, %	10.5	NB/SH/T 0824-2010
Nitrogen content, %	2.0	NB/SH/T 0656-2017

Note: The above analytical data are not specifications.

PERFORMANCE CHARACTERISTICS

- Ashless anti-wear additive with excellent oxidation resistance
- Can be used as a substitute for ZDDP in the formulation of zinc-free metalworking fluids and industrial oils
- Often compounded with sulfur additives for use in metalworking applications

APPLICATION

- Metalworking fluids, broaching oil
- Deep-hole drilling oil, machining oil
- Hydraulic oil, industrial gear oil
- Greases

USAGE METHOD

- Added to the formulation directly and compatibility needs to be tested before adding
- Recommended dosage: 0.4-5.0 wt%

RELATIVE PRODUCTS

RC 3880

PACKAGING AND STORAGE

Packaging	50kg plastic drum or 180kg steel drum (Net weight)	
Storage conditions	Store in a cool, dry, well-ventilated warehouse	

HANDLING INFORMATION

Avoid contact with skin, eyes and clothing. Operate in accordance with good industrial health and safety practices. Please refer to material safety data sheet (MSDS) for additional handling information on *PSAIL**3880.

Luoyang Pacific United Petrochemical Co., Ltd. (UNPChemicals) hopes that the information provided will be helpful to you. The information provided in this document has been prepared by technicians and is true and accurate as of the date of this document. However, please note that the conditions of your use and application of our products, technical assistance and information (whether orally, in writing or through product evaluation), including any suggested formulations and recommendations, are outside our control. UNPChemicals makes no representations, warranties or warranties (whether express, implied, statutory or otherwise), or implied warranties as to the completeness, accuracy or timeliness of any information. It is therefore important that you test our products, technical assistance and information, including how they are packaged, to determine their performance, efficacy and safety. You are solely responsible for the performance, efficacy and safety of any products you produce. UNPChemicals assumes no liability and you bear all risks and liabilities for any use or handling of any material. Nothing in this document should be interpreted as suggesting the use of any product that conflicts with the patent covering any material or its use. No license is implied or granted under the claims of any patent. We will provide consistent quality products within our sales conditions.

Technical Data Sheet Page 2 of 2 Version 202412