

PSAIL® 374I is an amine phosphate salt-based EP/Anti-wear additive with antioxidant effects. Typically formulated with sulfur additives, it is extensively applied in metalworking fluids.

CHEMICAL COMPOSITION

Amine-neutralized butyl phosphate ester

CAS No.: 98679-19-7

TYPICAL PROPERTIES

Test Item	Typical Data	Method
Appearance	Yellow viscous liquid	Visual inspection
Density at 20°C, g/cm ³	0.96	GB/T 1884-2000
Viscosity at 40°C, mm ² /s	5428.1	GB/T 265-1988
Flash point open cup, °C	150.0	GB/T 3536-2008
Phosphorus content, %	7.7	NB/SH/T 0824-2010
Nitrogen content, %	3.3	NB/SH/T 0656-2017

Note: The above analytical data are not specifications.

PERFORMANCE CHARACTERISTICS

- Compatible with sulfur additives for wide application in metalworking fluids
- Provides extreme-pressure (EP) and anti-wear performance with secondary antioxidant properties

APPLICATION

- Metalworking fluids for medium to harsh machining
- Honing oil
- Grinding oils
- Broaching oil
- Deep-hole drilling oils

USAGE METHOD

- Added to the formulation directly and compatibility needs to be tested before adding
- Recommended dosage: 0.2-1.5%

RELATIVE PRODUCTS

- RC 3741

PACKAGING AND STORAGE

Packaging	50kg plastic drum or 200kg steel drum (Net weight)
Storage conditions	Store in a cool, dry, well-ventilated warehouse

HANDLING INFORMATION

Avoid contact with skin, eyes and clothing. Operate in accordance with good industrial health and safety practices. Please refer to material safety data sheet (MSDS) for additional handling information on **PSAIL®3741**.

Luoyang Pacific United Petrochemical Co., Ltd. (UNPChemicals) hopes that the information provided will be helpful to you. The information provided in this document has been prepared by technicians and is true and accurate as of the date of this document. However, please note that the conditions of your use and application of our products, technical assistance and information (whether orally, in writing or through product evaluation), including any suggested formulations and recommendations, are outside our control. UNPChemicals makes no representations, warranties or warranties (whether express, implied, statutory or otherwise), or implied warranties as to the completeness, accuracy or timeliness of any information. It is therefore important that you test our products, technical assistance and information, including how they are packaged, to determine their performance, efficacy and safety. You are solely responsible for the performance, efficacy and safety of any products you produce. UNPChemicals assumes no liability and you bear all risks and liabilities for any use or handling of any material. Nothing in this document should be interpreted as suggesting the use of any product that conflicts with the patent covering any material or its use. No license is implied or granted under the claims of any patent. We will provide consistent quality products within our sales conditions.