

# EXTREME PRESSURE ANTI-WEAR AGENTS

**PSAIL® SERIES** 

Luoyang Pacific United Petrochemical Co., Ltd.

UNPChemicals

No. 113, Huayang Avenue, Baihe Town,

Mengjin District, Luoyang City

Henan Province, China

+86-379-67877555 sales@unpchemicals.com

www.unpchemicals.com

*PSAIL® 3740* is an amine-neutralized fatty alcohol phosphate ester structure that serves as an efficient ashless anti-wear and extreme pressure additive, playing a crucial role in the field of metalworking fluids. This additive is commonly used in conjunction with sulfur-containing additives, effectively enhancing the surface finish of workpieces and significantly extending the tool life under various working conditions.

## **CHEMICAL COMPOSITION**

Amine-neutralized butyl phosphate ester (T308) CAS No.: 96690-34-5

#### **TYPICAL PROPERTIES**

Test Item	Typical Data	Method
Appearance	Yellow viscous liquid	Visual inspection
Density at 20℃, g/cm³	0.97	GB/T 1884-2000
Flash point open cup, ℃	150.0	GB/T 3536-2008
Phosphorus content, %	9.5	NB/SH/T 0824-2010
Nitrogen content, %	3.9	NB/SH/T 0656-2017

Note: The above analytical data are not specifications.

#### PERFORMANCE CHARACTERISTICS

- Ashless, excellent extreme pressure and anti-wear performance
- Combined with sulfur additives it can improve the surface finish of the workpiece and extend the service life of the tool

### **APPLICATION**

- Metalworking fluids for medium to harsh machining
- Honing oil
- Grinding oils
- Broaching oil
- Deep-hole drilling oils

#### **USAGE METHOD**

- Added to the formulation directly and compatibility needs to be tested before adding
- Recommended dosage: 0.2-1.5%

### **RELATIVE PRODUCTS**

RC 3740, VANLUBE 672, ELCO 670, T308

### **PACKAGING AND STORAGE**

Packaging	50kg plastic drum or 200kg steel drum (Net weight)	
Storage conditions	Store in a cool, dry, well-ventilated warehouse	

#### **HANDLING INFORMATION**

Avoid contact with skin, eyes and clothing. Operate in accordance with good industrial health and safety practices. Please refer to material safety data sheet (MSDS) for additional handling information on *PSAIL*®3740.

Luoyang Pacific United Petrochemical Co., Ltd. (UNPChemicals) hopes that the information provided will be helpful to you. The information provided in this document has been prepared by technicians and is true and accurate as of the date of this document. However, please note that the conditions of your use and application of our products, technical assistance and information (whether orally, in writing or through product evaluation), including any suggested formulations and recommendations, are outside our control. UNPChemicals makes no representations, warranties or warranties (whether express, implied, statutory or otherwise), or implied warranties as to the completeness, accuracy or timeliness of any information. It is therefore important that you test our products, technical assistance and information, including how they are packaged, to determine their performance, efficacy and safety. You are solely responsible for the performance, efficacy and safety of any products you produce. UNPChemicals assumes no liability and you bear all risks and liabilities for any use or handling of any material. Nothing in this document should be interpreted as suggesting the use of any product that conflicts with the patent covering any material or its use. No license is implied or granted under the claims of any patent. We will provide consistent quality products within our sales conditions.