


MSAIL® 300L as a liquid organic molybdenum friction modifier containing sulfur and phosphorus, it can greatly reduce the friction coefficient of oil products, and has multiple functions such as extreme pressure, anti-wear and anti-oxidation. It is widely used in internal-combustion engine oil, various industrial lubricants, pure oil metalworking fluid, grease, etc.

CHEMICAL COMPOSITION



Molybdenum dithiophosphate

CAS No.: 72030-25-2

TYPICAL PROPERTIES

Test Item	Typical Data	Method
Appearance	Brownish liquid	-
Density at 20°C, g/cm ³	1.05	GB/T 1884-2000
Flash point open cup, °C	162	GB/T 3536-2008
Molybdenum content, %	9.1	NB/SH/T 0824-2010
Sulphur content, %	11.3	NB/SH/T 0824-2010
Phosphorus content, %	3.2	NB/SH/T 0824-2010

Note: The above analytical data are not specifications

PERFORMANCE CHARACTERISTICS

- High molybdenum content, low phosphorus content
- Less odor, better oil solubility
- Excellent friction-reducing and anti-wear performance, excellent synergistic performance

APPLICATION

- Internal-combustion engine oil
- Various industrial lubricating oils
- Metal working fluids
- Lubricating grease

USAGE METHOD

- Added to the formulation directly and compatibility needs to be tested before adding
- Recommended treat level: 0.2-3.0wt%

RELATIVE PRODUCTS

- SAKURA LUBE 300, MOLYVAN L

PACKAGING AND STORAGE

Packaging	50kgs or 200kgs / Steel drum (Net weight)
Storage conditions	Store in a cool, dry, well-ventilated warehouse

HANDLING INFORMATION

Avoid contact with skin, eyes and clothing. Operate in accordance with good industrial health and safety practices. Please refer to material safety data sheet (MSDS) for additional handling information on **MSAIL® 300L**.

Luoyang United Pacific Petrochemical Co., Ltd. (UNPChemicals) hopes that the information provided will be helpful to you. The information provided in this document has been prepared by technicians and is true and accurate as of the date of this document. However, please note that the conditions of your use and application of our products, technical assistance and information (whether orally, in writing or through product evaluation), including any suggested formulations and recommendations, are outside our control. UNPChemicals makes no representations, warranties or warranties (whether express, implied, statutory or otherwise), or implied warranties as to the completeness, accuracy or timeliness of any information. It is therefore important that you test our products, technical assistance and information, including how they are packaged, to determine their performance, efficacy and safety. You are solely responsible for the performance, efficacy and safety of any products you produce. UNPChemicals assumes no liability and you bear all risks and liabilities for any use or handling of any material. Nothing in this document should be interpreted as suggesting the use of any product that conflicts with the patent covering any material or its use. No license is implied or granted under the claims of any patent. We will provide consistent quality products within our sales conditions.