

**FMET<sup>®</sup> T2** is an ashless friction modifier with an ethoxylated tallow amine structure (containing only C, H, O, N). It can greatly reduce the friction coefficient of oil products and is widely used in mineral-based and synthetic-based lubricant formulations. It is usually used in engine oils, automatic or manual transmission oil formulations. In the textile industry, it can also be used as an emulsifier, antistatic agent and dispersant. The product has a yellow liquid appearance and will solidify into a paste at low temperatures, both states can be used directly.

## CHEMICAL COMPOSITION

Ethoxylated tallow amine

CAS No.: 61791-44-4

## TYPICAL PROPERTIES

Test Item	Typical Data	Method
Appearance at 20℃	Paste solid	Visual inspection
Density at 20℃, g/cm <sup>3</sup>	0.90	GB/T1884-2000
Viscosity at 40℃, mm <sup>2</sup> /s	62.08	GB/T 265-1988
Base number, mgKOH/g	155	SH/T 0251-1993
Flash point closed cup, °C	150.2	GB/T 261-2021
Water content, %	0.05	GB/T 11133-2015

*Note: The above analytical data are not specifications.*

## PERFORMANCE CHARACTERISTICS

- Excellent anti-friction properties
- Free of metal, sulfate ash
- Good synergistic effect with various friction improvers including MoDTC

## APPLICATION

- Engine oil
- Automatic transmission fluid formulations
- Manual transmission fluid formulations

## **USAGE METHOD**

- Added to the formulation directly and compatibility needs to be tested before adding
- Recommended treat level: 0.3-1.0%

## **RELATIVE PRODUCTS**

- ETHOMEEN T12

## **PACKAGING AND STORAGE**

<b>Packaging</b>	50kg plastic drum or 180kg steel drum (Net weight)
<b>Storage conditions</b>	Store in a cool, dry, well-ventilated warehouse

## **HANDLING INFORMATION**

Avoid contact with skin, eyes and clothing. Operate in accordance with good industrial health and safety practices. Please refer to material safety data sheet (MSDS) for additional handling information on **FMET® T2**.

Luoyang Pacific United Petrochemical Co., Ltd. (UNPChemicals) hopes that the information provided will be helpful to you. The information provided in this document has been prepared by technicians and is true and accurate as of the date of this document. However, please note that the conditions of your use and application of our products, technical assistance and information (whether orally, in writing or through product evaluation), including any suggested formulations and recommendations, are outside our control. UNPChemicals makes no representations, warranties or warranties (whether express, implied, statutory or otherwise), or implied warranties as to the completeness, accuracy or timeliness of any information. It is therefore important that you test our products, technical assistance and information, including how they are packaged, to determine their performance, efficacy and safety. You are solely responsible for the performance, efficacy and safety of any products you produce. UNPChemicals assumes no liability and you bear all risks and liabilities for any use or handling of any material. Nothing in this document should be interpreted as suggesting the use of any product that conflicts with the patent covering any material or its use. No license is implied or granted under the claims of any patent. We will provide consistent quality products within our sales conditions.