Luoyang Pacific United Petrochemical Co., Ltd.

UNPChemicals

No. 113, Huayang Avenue, Baihe Town,

Mengjin District, Luoyang City

Henan Province, China

86-379-67877555 sales@unpchemicals.com

www.unpchemicals.com

CSAIL®T561 is a liquid ashless metal deactivator with extreme pressure and oxidation resistance effects. It is widely used in various automotive and industrial lubricating oils and metalworking fluids. At very low concentration, it can effectively prevent the corrosion of active sulfur on copper and copper alloys.

CHEMICAL COMPOSITION

$$H_{25}C_{12}$$
—S—S—S— $C_{12}H_{25}$

Thiadiazole tert-dodecyl mercaptan condensate CAS No.: 59656-20-1

TYPICAL PROPERTIES

| Test Item | Typical Data | Method |
|---------------------------|--------------------------|-------------------|
| Appearance | Brown transparent liquid | Visual inspection |
| Density at 20℃, g/cm³ | 1.03 | GB/T 1884-2000 |
| Viscosity at 100°C, mm²/s | 18.9 | GB/T 265-1988 |
| Flash point open cup, ℃ | 154 | GB/T 3536-2008 |
| Acid value, mgKOH/g | 4.1 | GB/T 7304-2014 |
| Sulfur content, % | 27.6 | GB/T 17040-2019 |

Note: The above analytical data are not specifications.

PERFORMANCE CHARACTERISTICS

- Low dosage, excellent oil solubility, low odor
- Excellent inhibition of active sulfur corrosion
- Excellent anti-oxidation synergistic performance

APPLICATION

- Various automotive and industrial lubricating oils, greases
- Metalworking fluids

USAGE METHOD

Added to the formulation directly and compatibility needs to be tested before adding

Recommended treat level: 0.1-0.5%

Grease: 1.0-2.5%

RELATIVE PRODUCTS

• T561

PACKAGING AND STORAGE

| Packaging | 50kg plastic drum or 200kg steel drum (Net weight) | |
|--------------------|--|--|
| Storage conditions | Store in a cool, dry, well-ventilated warehouse | |

HANDLING INFORMATION

Avoid contact with skin, eyes and clothing. Operate in accordance with good industrial health and safety practices. Please refer to material safety data sheet (MSDS) for additional handling information on *CSAIL®T561*.

Luoyang Pacific United Petrochemical Co., Ltd. (UNPChemicals) hopes that the information provided will be helpful to you. The information provided in this document has been prepared by technicians and is true and accurate as of the date of this document. However, please note that the conditions of your use and application of our products, technical assistance and information (whether orally, in writing or through product evaluation), including any suggested formulations and recommendations, are outside our control. UNPChemicals makes no representations, warranties or warranties (whether express, implied, statutory or otherwise), or implied warranties as to the completeness, accuracy or timeliness of any information. It is therefore important that you test our products, technical assistance and information, including how they are packaged, to determine their performance, efficacy and safety. You are solely responsible for the performance, efficacy and safety of any products you produce. UNPChemicals assumes no liability and you bear all risks and liabilities for any use or handling of any material. Nothing in this document should be interpreted as suggesting the use of any product that conflicts with the patent covering any material or its use. No license is implied or granted under the claims of any patent. We will provide consistent quality products within our sales conditions.